

Data sheet

Hydraulic data

Maximum operating pressure P_N	16 bar
Head max $H_{\max}$	4,0 m
Flow max $Q_{\max}$	15,5 m ³ /h
Minimum suction head at 50 °C m	3 m
Minimum suction head at 95 °C m	10 m
Minimum suction head at 110 °C	16 m
Min. fluid temperature $T_{\min}$	-10 °C
Max. fluid temperature $T_{\max}$	110 °C
Min. ambient temperature $T_{\min}$	-10 °C
Max. ambient temperature $T_{\max}$	40 °C

Motor data


Energy efficiency index (EEI)	0,19
Mains connection	1~230 V $\pm$ 10%, 50/60 Hz
Rated power P_2	99 W
Min. speed $n_{\min}$	750 1/min
Max. speed $n_{\max}$	2600 1/min
Power consumption $P_{1 \min}$	7 W
Power consumption $P_{1 \max}$	130 W
Interference emission	EN 61800-3;2004+A1;2012 /residential area (C1)
Interference immunity	EN 61800-3;2004+A1;2012 /industrial environment (C2)
Insulation class	F
Protection class	IPX4D

Installation dimensions

Pipe connection on the suction side DN_s	DN 40
Pipe connection on the pressure side DN_d	DN 40
Port-to-port length L_0	220 mm


Materials

Pump housing	Cast iron
Impeller	PPS-GF40
Shaft	Stainless steel
Bearing	Carbon-graphite


Pump curves

Dimensions and dimensions drawings

Stratos MAXO (2186270)




Stratos MAXO 40/0,5-4 PN 16



Wiring diagram

Standard: 1~ 230 V, 50/60 Hz, Option: 3~ 230 V, 50/60 Hz



SSM: Collective fault signal (NC contact in accordance with VDI 3814, load capacity 1 A, 250 V ~)