

Data sheet

Hydraulic data

Minimum efficiency index (MEI)	0,4
Maximum operating pressure <i>PN</i>	10 bar
Min. fluid temperature <i>T</i> _{min}	-20 °C
Max. fluid temperature <i>T</i> _{max}	120 °C
Min. ambient temperature <i>T</i> _{min}	0 °C
Max. ambient temperature <i>T</i> _{max}	40 °C

Motor data

Mains connection	3~380 V, 50/60 Hz
Motor efficiency class	IE4
Rated power <i>P</i> ₂	4 kW
Rated current <i>I</i> _N	12 A
Rated speed <i>n</i>	2900 1/min
Max. speed <i>n</i> _{max}	2900 1/min
Interference emission	EN 61800-3
Interference immunity	EN 61800-3
Insulation class	F
Protection class motor	IP55
Integrated full motor protection	-
Threaded cable connection	1 x M16x1.5

Materials

Pump housing	Cast iron
Impeller	PPE/PS-GF30
Shaft	Stainless steel
Shaft seal	AQ1EGG
Lantern	Cast iron

Approved liquids (other liquids upon request)

Heating water (as per VDI 2035)	yes
Heat carrier oil	Special version at additional charge
Cooling and cold water circulation systems	yes
Water-glycol mixtures (at 20 – 40 vol. % glycol and fluid temperature ≤ 40 °C)	yes

Installation dimensions

Port-to-port length <i>L0</i>	320 mm
Pipe connection on the suction side <i>DN_s</i>	DN 40
Pipe connection on the pressure side <i>DN_d</i>	DN 40