

Data sheet

Hydraulic data

Maximum operating pressure P_N	10 bar
Max. delivery head H	7,4 m
Max. volume flow Q	8,2 m ³ /h
Min. fluid temperature for HVAC applications $T_{\min}$	-20 °C
Max. fluid temperature for HVAC T	110 °C
Min. ambient temperature $T_{\min}$	0 °C
Max. ambient temperature $T_{\max}$	40 °C
Max. permitted total water hardness	3.57 mmol/l (20°dH)

Motor data

Energy efficiency index (EEI)	0,20
Mains connection	1~230 V, 50/60 Hz
Rated power P_2	0,09 kW
Rated current I_N	1 A
Min. speed $n_{\min}$	1000 1/min
Max. speed $n_{\max}$	3700 1/min
Power consumption $P_{1\min}$	5 W
Power consumption $P_{1\max}$	120 W
Interference emission	EN 61800-3;2004+A1;2012 /residential area (C1)
Interference immunity	EN 61800-3;2004+A1;2012 /industrial environment (C2)
Speed control	Frequency converter
Insulation class	F
Protection class motor	IPX4D
Motor protection	Internal protection overheating and overcurrent

Materials

Pump housing	Bronze
Impeller	PPS-GF40
Shaft	Stainless steel
Bearing	Carbon, synthetic resin-impregnated

Installation dimensions

Pipe connection on the suction side DNs	G 1½
Pipe connection on the pressure side DNd	G 1½
Port-to-port length LO	180 mm