

Data sheet

Hydraulic data

Maximum operating pressure P_N	10 bar
Flow max $Q_{\max}$	2,7 m ³ /h
Minimum suction head at 50 °C m	0,5 m
Minimum suction head at 95 °C m	3 m
Minimum suction head at 110 °C	10 m
Min. fluid temperature $T_{\min}$	-10 °C
Max. fluid temperature $T_{\max}$	95 °C
Max. fluid temperature for max. ambient temperature of +25 °C $T_{\max}$	95 °C
Max. fluid temperature for max. ambient temperature of +40 °C $T_{\max}$	95 °C
Min. ambient temperature $T_{\min}$	-10 °C
Max. ambient temperature $T_{\max}$	40 °C

Motor data

Energy efficiency index (EEI)	0,18
Mains connection	1~230 V $\pm$ 10%, 50/60 Hz
Min. speed $n_{\min}$	700 1/min
Max. speed $n_{\max}$	3400 1/min
Power consumption $P_{1\min}$	3 W
Power consumption $P_{1\max}$	20 W
Interference emission	EN 61000-6-3
Interference immunity	EN 61000-6-2
Electromagnetic compatibility	EN 61800-3
Threaded cable connection	1 x PG11
Insulation class	F
Protection class	IPX2D


Materials

Pump housing	Cast iron
Impeller	PP-GF40
Shaft	Stainless steel
Bearing	Carbon, metal-impregnated

Installation dimensions


Pipe connection on the pressure side DNd	G 1½
Pipe connection on the suction side DNs	G 1½
Port-to-port length LO	130 mm


Pump curves



Dimensions and dimensions drawings

4215514_ConGraph_yonos_pico_row_130_dim_01_1708



Wiring diagram

Blocking current-proof motor

Single-phase motor (EM) 2-pole - 1~230 V, 50 Hz